


Safety Barrier Technical Conditions for Use

SAFEZONE MDS Safety Barrier – Permanent & Temporary

	Issue Date: 1 September 2023	Supplier: Jaybro Group
	<p>These conditions take precedence over any instructions in the Product Manual.</p> <p>This document is a summary of the Austroads Safety Barrier Assessment Panel's assessment of the technical performance of the product against AS/NZS 3845 Parts 1 or 2 only. It does not consider procurement practices by individual Road Agencies.</p> <p>The Austroads Safety Assessment Panel may at any time, withdraw or modify this Technical Conditions for Use without notice.</p> <p>These acceptance conditions should be read in conjunction with the Product Manual and Austroads Guide to Road Design Part 6: Roadside Design, Safety and Barriers.</p> <p>Acceptance of this product does not place any obligation on the Northern Territory Government or its contractors, to purchase or use the product.</p>	

Status	Recommended for Acceptance
Product accepted	SAFEZONE MDS Safety Barrier <u>Variants</u> Variants that are NOT listed above are NOT recommended for acceptance.
Accepted impact speed	100 km/h
Product Manual reviewed	Ver.1.23
Product Manual	SafeZone+Manual v1.24 (intelligencebank.com)

Design Requirements

Containment Level	Point of Redirection		Tested Article Length (m)	Anchor/Post Spacing (m)	Dynamic Deflection (m)	Working Width (m)	Notes
	Leading (m)	Trailing (m)					
MASH TL3	Interface between barrier and end treatment		40.6	5.8	0.17	0.81	Refer system conditions

Approved Connections

An accepted end treatment must be provided at both ends of all barrier installations	
Public Domain Products	
W-Beam Guardrail	Not Permitted
Thrie-Beam Guardrail	Not Permitted
Concrete	Not Permitted

Proprietary Products	
UNIVERSAL TAU-M Crash Cushion	<ul style="list-style-type: none"> Refer Universal Tau-M Crash Cushion Technical Conditions for Use. The Safezone LDS to Universal Tau-M Crash Cushion transition must be used to connect the crash cushion to the barrier. Reverse impacts into the transition section can produce a greater occupant severity value than preferred. Where reverse impacts are possible (e.g. bi-directional traffic), a risk assessment must be completed and steps to mitigate the likelihood of reverse impact should be implemented.
ABSORB-M Crash Cushion	<ul style="list-style-type: none"> Permitted for temporary installations only The installation is restricted to an impact speed of 80 km/h or less. Refer to Absorb-M Crash Cushion Technical Conditions for Use. The Safezone MDS to Absorb-M Crash Cushion transition must be used to connect the crash cushion to the barrier. This is a gating device.

Design Guidance

Minimum installation length	40.6 metres between crash cushions/terminals (tested article)
System width (m)	0.639
Minimum distance to excavation (m)	0.50 (TL3) – measured from the outer edge of the foot on the works side
Side slope limit	8%
Systems conditions	<ol style="list-style-type: none"> Installation on top of a kerb is not recommended, however if installed on top of a kerb all system components must be free to operate. All offsets are to be measured from the relevant outer edge of the foot. The foot is not trafficable. This product is designed for constrained sites ONLY that cannot accommodate the working widths of more flexible systems. While providing lower working width, this product increases the potential for a vehicle occupant risk during high-speed impacts. Throughout the installation it is recommended to revert to greater pin spacing (LDS, Standard) where there is the accepted working width behind the installation. A risk assessment of using this product must be undertaken. Where the risk of high-speed impacts is high, the speed must be limited to not greater than 80km/h.
Gore area use	Permitted
Pedestrian area use	Permitted
Cycleway use	Permitted
Frequent impact likely	Permitted
Remote location	Permitted
Median use	Permitted

Foundation Pavement Conditions					
Pavement Type	Use	Max Accepted Impact Speed (km/h)	Post/Pin Spacing (m)	Post/Pin Type	Pavement Construction
Concrete	Permitted	100	5.8	M30 x 300mm threaded rod with epoxy	Min. 200 mm reinforced or 250 mm non-reinforced
Deep lift asphaltic concrete					Min. 250 mm
Asphaltic concrete over granular pavement					Min. 150 mm AC over 150 mm granular pavement (AASHTO standard soil strength)
Flush seal over granular pavement	Not Permitted				
Unsealed compacted formation					

Note: Installation in pavement conditions not permitted above have not been justified to the Panel's satisfaction.