

- 1. WHERE ROADS ARE IDENTIFIED TO CATER FOR WIDE LOADS ENSURE THAT MEDIANS AND TRAFFIC ISLANDS ARE PROVIDED NO HIGHER THAN 100mm.
 - WHERE KERBED ROADS HAVE A CARRIAGEWAY LESS THAN 8.0m IN WIDTH PROVIDE LAYBACK KERB TYPE 1 (LBK 1).

0	ISSUED AS A STANDARD DRAWING	FEB 2024	D.LLANO	DIPL			
No.	DESCRIPTION	DATE	NAME	DEPT/COMPANY			
AMENDMENTS							

WARNING

BEWARE OF UNDERGROUND SERVICES.
THE LOCATIONS OF UNDERGROUND SERVICES ARE
APPROXIMATE ONLY AND THEIR EXACT POSITION
SHOULD BE PROVEN ON SITE. NO GUARANTEE IS GIVEN
THAT ALL EXISTING SERVICES ARE SHOWN.

DRAWN	CHECKED
DIPL	DIPL
DATE	DATE
DESIGNED	CHECKED
DIPL	DIPL
DATE	DATE
DESIGN LEADER	DESIGN DIRECTOR
DIPL	DIPL
DATE	DATE

Northern Territory Government	V
	FILE

STANDARD DRAWINGS
TYPICAL CROSS SECTIONS

WIDE LOAD VEHICLE CLEARANCE REQUIREMENTS

FILE No.	ASSET No.	SHEET No.	DRAWING No.	AMEND.	SHEET
-	-	1 OF 1	CS3012	0	Ä1