


# Safety Barrier Technical Conditions for Use

## DB80 T150S Concrete Safety Barrier - Temporary

	<b>Issue Date:</b> 20 December 2021	<b>Proponent:</b> Jaybro Group
	<p><b>These conditions take precedence over any instructions in the Product Manual.</b> This document is a summary of the Austroads Safety Barrier Assessment Panel's assessment of the technical performance of the product against AS/NZS 3845 Parts 1 or 2 only. It does not consider procurement practices by individual Road Agencies.</p> <p>The Austroads Safety Assessment Panel may at any time, withdraw or modify this Technical Conditions for Use without notice.</p> <p>These acceptance conditions should be read in conjunction with the Product Manual and Austroads Guide to Road Design Part 6: Roadside Design, Safety and Barriers.</p> <p>Acceptance of this product does not place any obligation on the Northern Territory Government or its contractors, to purchase or use the product.</p>	

Status	<b>Recommended for Acceptance</b>
Product accepted	DB80 T150S Concrete Safety Barrier
	<p><u>Variants</u></p> <p>Variants that are NOT listed above are NOT recommended for acceptance.</p>
Accepted impact speed	100 km/h
Product manual reviewed	V1.8
Product Manual	<a href="https://www.jaybro.com.au/deltabloc-db80-concrete-safety-barrier-6.html">https://www.jaybro.com.au/deltabloc-db80-concrete-safety-barrier-6.html</a>

### Design Requirements

Containment Level	Point of Redirection		Tested Article Length (m)	Anchor/Post Spacing (m)	Dynamic Deflection (m)	Working Width (m)	Notes
	Leading (m)	Trailing (m)					
MASH TL3	0	0	92	Anchored at ends only	0.81	1.36	
MASH TL4	32.30	59.70	92	Anchored at ends only	0.81	2.50	

### Approved Connections

<b><i>An accepted end treatment must be provided at both ends of all barrier installations</i></b>	
<b>Public Domain Products</b>	
W-Beam Guardrail	Not permitted
Thrie-Beam Guardrail	Not permitted
Concrete	Not permitted
<b>Proprietary Products</b>	

UNIVERSAL TAU-M Crash Cushion	<ul style="list-style-type: none"> <li>• Refer Universal Tau-M Crash Cushion Technical Conditions for Use.</li> <li>• The DB80 T150S to Universal TAU-M Crash Cushion transition must be used to connect the crash cushion to the barrier.</li> <li>• Reverse impacts into the transition section can produce a greater occupant severity value than preferred. Where reverse impacts are possible (e.g. bi-directional traffic), a risk assessment must be completed and steps to mitigate the likelihood of reverse impact should be implemented.</li> </ul>
QUADGUARD M10 CZ Crash Cushion	<ul style="list-style-type: none"> <li>• Refer to QUADGUARD M10 CZ Crash Cushion Technical Conditions for Use.</li> <li>• The DB80 T150S transition to end terminal must be used to connect the crash cushion to the barrier.</li> <li>• Reverse impacts into the transition section can produce a greater occupant severity value than preferred. Where reverse impacts are possible (e.g. bi-directional traffic), a risk assessment must be completed and steps to mitigate the likelihood of reverse impact should be implemented.</li> </ul>

**Design Guidance**

Minimum installation length	92 metres between crash cushions/terminals (tested article)
System width (m)	0.57
Minimum distance to excavation (m)	0.81 – measured from the face of the barrier on the works side (TL3 & TL4)
Side slope limit	10%
System conditions	<ol style="list-style-type: none"> <li>1. The system is anchored at the ends only</li> <li>2. Installation on top of a kerb is not recommended</li> </ol>
Gore area use	Permitted
Pedestrian area use	Permitted
Cycleway use	Permitted
Frequent impact likely	Permitted
Remote location	Permitted
Median use	Permitted

Foundation Pavement Conditions					
Pavement Type	Use	Max Accepted Impact Speed (km/h)	Post/Pin Spacing (m)	Post/Pin Type	Pavement Construction
Concrete	Permitted	100			<p align="center"><u>Freestanding – Anchored at Ends Only</u></p> <p>Foundation pavement conditions must be smooth and free of snag points, kerbs or obstruction that may interfere with the operation of the product</p>
Deep lift asphaltic concrete					
Asphaltic concrete over granular pavement					
Flush seal over granular pavement					
Unsealed compacted formation					

**Note: Installation in pavement conditions not permitted above have not been justified to the Panel's satisfaction.**